

View Online at <https://aerobasegroup.com/nsn/5935-01-041-3666>

Body Style:

Straight edge type w/mounting flange

Overall Length:

1.550 inches

Overall Height:

0.270 inches

Overall Width:

0.160 inches

Environmental Protection:

Humidity resistant and shock proof and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.080 inches

Distance Between Mounting Facility Centers:

1.250 inches

Board Accommodated Length:

1.050 inches single board

Board Accommodated Width:

0.031 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

0.5 single mating end single contact grouping

Polarization Method:

Contact

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy 172 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic phenolic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-533, alloy 172 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-1, ty mfh military specification single material response single mating end

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.