NSN 5935-01-042-0128

Electrical Receptacle Connector - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5955-01-042-0126
Body Style:
Straight shape
Overall Length:
1.385 inches
Overall Height:
0.170 inches
Overall Width:
3.028 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and corrosion resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.276 inches and 0.286 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.558 inches and 0.566 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 2.574 inches and 2.582 inches
Distance From Mounting Shoulder To Front Face:
Between 0.519 inches and 0.534 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
51 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 200.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-042-0128

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074, grade a, cl 3 or 4 military specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Included Contact Quantity:
51 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Furnished items - spare contact
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.051 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-83733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-83733/1 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.