## NSN 5935-01-042-1859

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-042-1859 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.150 inches **Overall Diameter:** 0.880 inches **Environmental Protection:** Shock proof and vibration resistant **Cable Entrance Diameter:** 0.100 inches **Mounting Facility Thickness:** 0.350 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Compression nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 75.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** 

Tin single mating end single contact grouping

**Insert Material:** 

Plastic tetrafluoroethylene single mating end

## NSN 5935-01-042-1859

Electrical Receptacle Connector - Page 2 of 2



reriiii	ıaı ı	ype:	
Solder	well	single	ma

Solder well single mating end single contact grouping

**Included Contact Quantity:** 

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/flat

**Included Contact Type:** 

Coaxial socket single mating end single contact grouping

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A039b0