## NSN 5935-01-042-5086

Straight shape, external coupling w/backshell

Thread Class: 2a and 2a

**Body Style:** 

**Overall Length:** 

**Thread Direction:** 

Right-hand and right-hand

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-042-5086

3.920 inches
Overall Diameter:
2.200 inches
Environmental Protection:
Waterproof
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
16 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
0.0
Connector Locking Method:
Connector Locking Method:
Connector Locking Method:  Externally threaded shell
Connector Locking Method:  Externally threaded shell  Thread Length:
Connector Locking Method:  Externally threaded shell  Thread Length:  0.870 inches
Connector Locking Method:  Externally threaded shell  Thread Length:  0.870 inches  Thready Qty Per Inch (tpi):
Connector Locking Method:  Externally threaded shell  Thread Length:  0.870 inches  Thready Qty Per Inch (tpi):  20 and 12
Connector Locking Method:  Externally threaded shell  Thread Length: 0.870 inches  Thready Qty Per Inch (tpi): 20 and 12  Thread Size:
Connector Locking Method:  Externally threaded shell  Thread Length:  0.870 inches  Thready Qty Per Inch (tpi):  20 and 12  Thread Size:  0.250 inches and 1.500 inches
Connector Locking Method:  Externally threaded shell  Thread Length: 0.870 inches  Thready Qty Per Inch (tpi): 20 and 12  Thread Size: 0.250 inches and 1.500 inches  Terminal Location:
Connector Locking Method:  Externally threaded shell  Thread Length: 0.870 inches  Thready Qty Per Inch (tpi): 20 and 12  Thread Size: 0.250 inches and 1.500 inches  Terminal Location:  Back single mating end single contact grouping
Connector Locking Method:  Externally threaded shell  Thread Length:  0.870 inches  Thready Qty Per Inch (tpi):  20 and 12  Thread Size:  0.250 inches and 1.500 inches  Terminal Location:  Back single mating end single contact grouping  Contact Material:
Connector Locking Method:  Externally threaded shell  Thread Length:  0.870 inches  Thready Qty Per Inch (tpi):  20 and 12  Thread Size:  0.250 inches and 1.500 inches  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping
Connector Locking Method:  Externally threaded shell  Thread Length: 0.870 inches  Thready Qty Per Inch (tpi): 20 and 12  Thread Size: 0.250 inches and 1.500 inches  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Gold single mating end single contact grouping  Insert Material:
Connector Locking Method:  Externally threaded shell  Thread Length:  0.870 inches  Thready Qty Per Inch (tpi):  20 and 12  Thread Size:  0.250 inches and 1.500 inches  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Gold single mating end single contact grouping

## NSN 5935-01-042-5086

Electrical Plug Connector - Page 2 of 2



## **Terminal Type:** Solder well single mating end single contact grouping **Included Contact Quantity:** 16 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.016 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A039b0