Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-043-2991

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
4.281 inches
Overall Diameter:
1.720 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Cable Entrance Diameter:
Between 1.065 inches and 1.085 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
24-10 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
73.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
18
Thread Size:
1.500 inches

NSN 5935-01-043-2991 Electrical Plug Connector - Page 2 of 2



B	ack single mating end single contact grouping
	ontact Surface Treatment:
	ilver single mating end single contact grouping
	isert Material:
	ubber single mating end
	ontact Surface Treatment Specification:
	q-s-365 federal specification single treatment response single mating end single contact grouping
	erminal Type:
	older well single mating end single contact grouping
	hell Material:
	luminum alloy
	hell Surface Treatment:
	admium
	hell Surface Treatment Specification:
	q-p-416, type 2, cl 3 federal specification single treatment response
	cluded Contact Quantity:
7	single mating end single contact grouping
In	cluded Contact Type:
R	ound socket single mating end single contact grouping
P	recious Material And Location:
С	ontact surfaces silver
P	recious Material And Weight:
0.	035 silver grains, troy
P	recious Material:
Si	ilver
τI	hread Series Designator:
U	nef
S	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
Ν	0
Fi	iig:
A	039b0