NSN 5935-01-043-7356

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-043-7356 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.250 inches **Overall Height:** 0.570 inches **Overall Width:** 0.290 inches **Distance Between Mounting Facility Centers:** 1.000 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 5.0 single mating end all contact groupings **Polarization Method:** Guide pin/socket **Insert Position In Deg:** 0.0 Thready Qty Per Inch (tpi): 56 Thread Size: 0.086 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and nickel single mating end all contact groupings **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end all contact groupings **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

NSN 5935-01-043-7356

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 26 single mating end all contact groupings **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surface gold **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):