## NSN 5935-01-044-1609

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-044-1609

Body Style:
Straight shape, internal coupling
Overall Length:
1.707 inches
Overall Diameter:
1.516 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
20-41 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Potting
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Potting type
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Crimp single mating end single contact grouping

**Shell Material:** Aluminum alloy

## NSN 5935-01-044-1609

Electrical Plug Connector - Page 2 of 2



## Shell Surface Treatment:

Cadmium and chromate

**Included Contact Quantity:** 

41 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surface gold and contact surface silver

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A039b0