NSN 5935-01-044-2346

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-044-2346

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape

Overall Length:

1.050 inches

Overall Height:

0.915 inches

Overall Width:

0.250 inches

Environmental Protection:

Dripproof and salt water resistant and shock proof and thermal shock resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

56 and 56

Thread Size:

0.086 inches and 0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end or plastic phenolic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping

NSN 5935-01-044-2346

Electrical Plug Connector - Page 2 of 2



Terminal Type:	
Crimp single mating en	d single contact grouping
Insert Material Specifi	cation:
Mil-p-19833 military sp	ecification single material response single mating end or mil-m-14 military specification single material response single
mating end	
Included Contact Qua	ntity:
14 single mating end si	ngle contact grouping
Included Contact Typ	e:
Round socket single ma	ating end single contact grouping
Precious Material And	I Location:
Contact surface gold	
Precious Material And	l Weight:
0.014 gold grains, troy	
Precious Material:	
Gold	
Thread Series Design	ator:
Unc and unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Stand	lard):
Mil-g-45204 spec.	