## NSN 5935-01-044-2353

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-044-2353

**Body Style:** 

Rectangular shape

**Overall Length:** 

5.358 inches

**Overall Height:** 

0.323 inches

**Body Width:** 

0.320 inches

**Environmental Protection:** 

Moisture proof and shock proof and vibration resistant

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end all contact groupings

**Polarization Method:** 

Contact

**Terminal Location:** 

Side single mating end 4th contact grouping

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings and nickel single mating end all contact groupings

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Tab, solder lug single mating end all contact groupings

**Contact Material Specification:** 

Qq-b750 federal specification single material response single mating end all contact groupings

**Insert Material Specification:** 

Mil-p-19833, gdi-30f military specification single material response single mating end or mil-m-14, sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

51 single mating end 2nd contact grouping

**Included Contact Type:** 

Flat socket single mating end all contact groupings

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.051 gold grains, troy

## NSN 5935-01-044-2353

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-p-19833 spec.