

View Online at <https://aerobasegroup.com/nsn/5935-01-044-4011>

Thread Class:

2a and 2a

Thread Direction:

Left-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.675 inches

Overall Diameter:

Between 2.859 inches and 2.891 inches

Environmental Protection:

Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

36-10 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

16 and 10

Thread Size:

2.312 inches and 2.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade a, cl 1 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate and nickel

Shell Surface Treatment Specification:

Qq-p-416, type 2 federal specification 1st treatment response and qq-p-416, type 2 federal specification 2nd treatment response and qq-n-290 federal specification 3rd treatment response or mil-c-26074 military specification 3rd treatment response

Included Contact Quantity:

48 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.048 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns and double stub

Specification Data:

96906-ms17345 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.