NSN 5935-01-044-4016

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-044-4016

Body Style:
Straight shape
Overall Length:
0.935 inches
Overall Width:
0.305 inches
Environmental Protection:
Moisture proof and salt water resistant and shock proof and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.088 inches and 0.094 inches
Distance Between Mounting Facility Centers:
0.715 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
15 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:

Included Contact Type:

Round pin single mating end single contact grouping

15 single mating end single contact grouping

NSN 5935-01-044-4016

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0