Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-044-4017

| View Online at https://aerobasegroup.com/nsn/5935-01-044-4017 |
|---|
| Body Style: |
| Straight shape |
| Overall Length: |
| 1.085 inches |
| Overall Width: |
| 0.305 inches |
| Environmental Protection: |
| Moisture proof and salt water resistant and shock proof and vibration proof |
| Unthreaded Mounting Hole Diameter: |
| Between 0.088 inches and 0.094 inches |
| Distance Between Mounting Facility Centers: |
| 0.865 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 21 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end single contact grouping |
| Polarization Method: |
| Mating end |
| Shell Type: |
| Solid |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium and chromate |
| Included Contact Quantity: |
| 21 single mating end single contact grouping |
| Included Contact Type: |
| Deved his single motion and single contest growning |

Round pin single mating end single contact grouping



Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.021 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: --Demilitarization: No

A039b0