## NSN 5935-01-044-4438

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-044-4438

**Body Style:** 

Straight edge type w/card guide

**Overall Length:** 

1.219 inches

**Overall Width:** 

0.340 inches

**Body Height:** 

0.458 inches

**Environmental Protection:** 

Humidity resistant and moisture proof and salt water resistant and vibration proof

**Board Accommodated Length:** 

1.100 inches single board

**Board Accommodated Width:** 

0.062 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

830.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

12 single mating end single contact grouping

**Included Contact Type:** 

Leaf spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-01-044-4438

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.012 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.