

View Online at <https://aerobasegroup.com/nsn/5935-01-044-4448>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

T-shape

Overall Length:

1.780 inches

Overall Height:

1.250 inches

Overall Width:

0.656 inches

Environmental Protection:

Salt water resistant and moisture resistant and vibration resistant and shock proof and thermal shock resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

3

Contact Position Arrangement Style:

N all mating ends

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 all mating ends all contact groupings

Contact Maximum Frequency Rating:

11000.0 megahertz all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thread Length:

0.172 inches and 0.202 inches

Thread Size:

0.625 inches

Contact Surface Treatment:

Gold all mating ends all contact groupings

Shell Material:

Copper alloy

Included Contact Quantity:

3 all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.003 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-a-55339 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-a-55339/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0