NSN 5935-01-044-5635

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-044-5635

Thread Class: 2a Thread Direction: Right-hand Body Style: Straight shape, internal coupling Overall Length: 1.234 inches Overall Diameter: 1.641 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Thread Direction: Right-hand Body Style: Straight shape, internal coupling Overall Length: 1.234 inches Overall Diameter: 1.641 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Right-hand Body Style: Straight shape, internal coupling Overall Length: 1.234 inches Overall Diameter: 1.641 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Body Style: Straight shape, internal coupling Overall Length: 1.234 inches Overall Diameter: 1.641 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Straight shape, internal coupling Overall Length: 1.234 inches Overall Diameter: 1.641 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Overall Length: 1.234 inches Overall Diameter: 1.641 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
1.234 inches Overall Diameter: 1.641 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Overall Diameter: 1.641 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
1.641 inches Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Environmental Protection: Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Moisture resistant and vibration resistant and salt water resistant Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Threaded Device Type: Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Back shell Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Mating End Quantity: 1 Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Contact Position Arrangement Style: 21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
21-16 single mating end Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Contact Removability: Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Removable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Polarization Method: Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Keyway or multiple keyway Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Insert Position In Deg: 330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
330.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Bayonet latch Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Thread Length: 0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
0.219 inches Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
Thread Size: 1.188 inches Terminal Location: Back single mating end single contact grouping
1.188 inches Terminal Location: Back single mating end single contact grouping
Terminal Location: Back single mating end single contact grouping
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy

NSN 5935-01-044-5635Electrical Plug Connector - Page 2 of 2

A039b0



Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
16 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.016 gold grains, troy and 0.016 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: