Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-044-5642

### Thread Class:

2a and 2a

### **Thread Direction:**

Right-hand and right-hand

### Body Style:

Straight shape, external coupling w/backshell

#### **Overall Length:**

1.969 inches

#### **Overall Height:**

1.750 inches

**Overall Width:** 

1.750 inches

#### **Environmental Protection:**

Fireproof and heat resistant

#### **Unthreaded Mounting Hole Diameter:**

#### Between 0.175 inches and 0.181 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.375 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

#### Distance From Mounting Shoulder To Front Face:

Between 0.812 inches and 0.828 inches

#### **Threaded Device Type:**

Back shell and coupling facility

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

24-22 single mating end

## Contact Removability:

Removable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

46.0 single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

## Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

## **Polarization Method:**

Keyway or multiple keyway

# Insert Position In Deg:

0.0

Shell Type:

Solid



**Connector Locking Method:** Externally threaded shell **Thread Length:** 0.625 inches Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 1.437 inches and 1.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Ceramic single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Stainless steel **Included Contact Quantity:** 4 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef and unef Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0