

View Online at <https://aerobasegroup.com/nsn/5935-01-044-8624>

**Body Style:**

Straight type

**Overall Length:**

4.350 inches

**Overall Height:**

0.715 inches

**Overall Width:**

0.250 inches

**Distance Between Mounting Facility Centers:**

4.100 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Glass single mating end and plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-14548, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Guide Design And Location:**

D shape pin right-hand at 12 oclock

**Insert Material Specification:**

Mil-p-19833 military specification single material response single mating end or mil-m-14 type sdg military specification single material response single mating end

**Included Contact Quantity:**

70 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.070 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-14548 spec.