Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-044-8645

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.429 inches
Overall Height:
Between 1.209 inches and 1.230 inches
Overall Width:
Between 1.209 inches and 1.230 inches
Environmental Protection:
Humidity resistant and shock proof and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.964 inches and 0.974 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.964 inches and 0.974 inches
Distance From Mounting Shoulder To Front Face:
Between 0.855 inches and 0.865 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
16-42 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Size:
0.938 inches
Terminal Location:
Back single mating end single contact grouping



Contact Material: Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl c federal specification single treatment response **Included Contact Quantity:** 42 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.042 gold grains, troy and 0.042 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0