NSN 5935-01-044-8679

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-044-8679

Body Style:

Straight edge type w/mounting flange

Overall Length:

4.356 inches

Overall Height:

0.656 inches

Overall Width:

0.325 inches

Environmental Protection:

Solvent resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

4.029 inches

Board Accommodated Length:

3.576 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1800.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Glass single mating end and plastic polyamide single mating end

Terminal Type:

Pin single mating end single contact grouping

Included Contact Quantity:

44 single mating end single contact grouping

NSN 5935-01-044-8679

Electrical Receptacle Connector - Page 2 of 2



| Inc | luded | d Con | tact | Type: |
|-----|-------|---------------|------|-------|
| | IUUC | 4 O OH | ıavı | IVDC. |

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.044 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0