Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-044-9215

Thread CI	ass:
2a	
Thread Di	rection:
Right-hand	t de la construcción de la const
Body Styl	e:
Straight sh	nape, external coupling
Overall Le	ength:
Between 1	.172 inches and 1.222 inches
Overall He	eight:
Between 1	.242 inches and 1.258 inches
Overall W	idth:
Between 1	.242 inches and 1.258 inches
Environm	ental Protection:
Moisture re	esistant and salt water resistant and shock proof and vibration resistant
Unthreade	ed Mounting Hole Diameter:
Between 0	0.116 inches and 0.126 inches
Center To	Center Distance Between Mounting Facilities Parallel To Height:
Between 0	0.964 inches and 0.974 inches
Distance	Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0	0.964 inches and 0.974 inches
Distance	From Mounting Shoulder To Front Face:
Between 0	0.765 inches and 0.775 inches
Threaded	Device Type:
Back shell	
Mating En	nd Quantity:
1	
Contact P	Position Arrangement Style:
16-07 sing	le mating end
Contact R	emovability:
Removable	e single mating end single contact grouping
Polarizatio	on Method:
Keyway or	multiple keyway
Insert Pos	sition In Deg:
225.0 and	190.0 and 160.0 and 50.0
Shell Type	e:
Solid	
Connecto	r Locking Method:
Bayonet pi	in
Thready C	Qty Per Inch (tpi):
28	
Thread Si	ze:
1.000 inch	es

Electrical Receptacle Connector - Page 2 of 2



Terminal Location: Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204, type 1, cl 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy 6061 **Shell Surface Treatment:** Chromium **Shell Material Specification:** Qq-a-367, t6 federal specification single material response **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold **Precious Material And Weight:** 0.007 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Un **Specification Data:** 81349-mil-c-81511/51 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard):

Mil-g-45204 spec.