Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-044-9218

| Thre | ead Class:   |
|------|--|
| 2a   |  |
| Thre | ead Direction:   |
| Rigł | nt-hand  |
| Ũ    | ly Style:  |
|      | ight shape, external coupling  |
|      | erall Length:  |
|      | ween 1.172 inches and 1.222 inches   |
| Ονε  | erall Height:  |
| Betv | ween 1.335 inches and 1.351 inches   |
| Ove  | erall Width:   |
| Betv | ween 1.335 inches and 1.351 inches   |
| Env  | ironmental Protection:   |
| Mois | sture resistant and salt water resistant and shock proof and vibration resistant |
| Unt  | hreaded Mounting Hole Diameter:  |
| Betw | ween 0.116 inches and 0.126 inches   |
| Cen  | ter To Center Distance Between Mounting Facilities Parallel To Height:           |
| Betv | ween 1.057 inches and 1.067 inches   |
| Dist | ance Between Centerlines Of Mounting Facilities Parallel To Body Width:          |
| Betv | ween 1.057 inches and 1.067 inches   |
| Dist | ance From Mounting Shoulder To Front Face:                                       |
| Betv | ween 0.765 inches and 0.775 inches   |
| Thre | eaded Device Type:   |
| Bac  | k shell  |
| Mat  | ing End Quantity:  |
| 1    |  |
| Con  | ntact Position Arrangement Style:  |
| 18-3 | 38 single mating end   |
| Con  | ntact Removability:  |
| Ren  | novable single mating end single contact grouping                                |
| Pola | arization Method:  |
| Key  | way or multiple keyway   |
| Inse | ert Position In Deg:   |
| 294  | .0 and 220.0 and 160.0 and 103.0   |
| She  | II Туре:   |
| Soli | d  |
| Con  | nnector Locking Method:  |
| Bay  | onet pin   |
| Thre | eady Qty Per Inch (tpi):   |
| 28   |  |
| Thre | ead Size:  |
| 1.12 | 25 inches  |

Electrical Receptacle Connector - Page 2 of 2



**Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204, type 1, cl 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy 6061 **Shell Surface Treatment:** Chromium **Shell Material Specification:** Qq-a-367, t6 federal specification single material response **Included Contact Quantity:** 38 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surface gold **Precious Material And Weight:** 0.038 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Un **Specification Data:** 81349-mil-c-81511/51 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.