## NSN 5935-01-044-9625



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-044-9625 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.290 inches **Overall Height:** 1.688 inches **Overall Width:** 1.688 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.157 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.336 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.336 inches **Distance From Mounting Shoulder To Front Face:** Between 0.785 inches and 0.790 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 94-31722 94-41722 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 30.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

Thread Length:

0.219 inches

**Operating Tempurature Rating:** 

Between -65.0 degrees celsius and 175.0 degrees celsius

## NSN 5935-01-044-9625

Mil-c-38999 spec.

Electrical Receptacle Connector - Page 2 of 2



Features Provided:
Pre-tinned terminal
Thread Size:
1.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
21 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.021 gold grains, troy and 0.021 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):