

View Online at <https://aerobasegroup.com/nsn/5935-01-045-4278>

**Body Style:**

Straight shape, flush mount

**Overall Length:**

1.061 inches

**Overall Height:**

3.075 inches

**Overall Width:**

2.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

2.783 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.437 inches

**Distance From Mounting Shoulder To Front Face:**

0.060 inches

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

67 2nd mating end

**Contact Removability:**

Removable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:**

7.5 2nd mating end 2nd contact grouping

**Polarization Method:**

2 polarization posts

**Shell Type:**

Solid

**Terminal Location:**

Back all mating ends all contact groupings

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold all mating ends all contact groupings

**Insert Material:**

Plastic diallyl phthalate all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response all mating ends all contact groupings

**Terminal Type:**

Crimp all mating ends all contact groupings

**Contact Material Specification:**

Qq-c-533 federal specification single material response all mating ends all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Insert Material Specification:**

Mil-m-14 military specification all material responses all mating ends

**Included Contact Type:**

Round pin all mating ends all contact groupings

**Special Features:**

Polarized at position 25

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.124 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.