**Thread Class:** 

Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-045-8070



## 2b **Thread Direction: Right-hand Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** 3.010 inches **Overall Diameter:** 1.250 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Cable Entrance Diameter:** 0.531 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16s-6 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 270.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp Thready Qty Per Inch (tpi): 20 **Thread Size:** 1.000 inches

## NSN 5935-01-045-8070

Electrical Plug Connector - Page 2 of 2



**Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Shell Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification all treatment responses **Included Contact Quantity:** 3 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.003 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0