NSN 5935-01-045-8109

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-045-8109 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.429 inches **Overall Height:** Between 1.428 inches and 1.449 inches **Overall Width:** Between 1.428 inches and 1.449 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** Between 0.855 inches and 0.865 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 20-2 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 330.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Thread Size:** 1.188 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-045-8109

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



| Contact Material: | |
|---|----|
| Copper alloy single mating end single contact grouping | |
| Contact Surface Treatment: | |
| Gold single mating end single contact grouping and silver single mating end single contact grouping | ng |
| Terminal Type: | |
| Crimp single mating end single contact grouping | |
| Shell Material: | |
| Aluminum alloy | |
| Shell Surface Treatment: | |
| Cadmium | |
| Shell Surface Treatment Specification: | |
| Qq-p-416, type 2, class c federal specification single treatment response | |
| Included Contact Quantity: | |
| 65 single mating end single contact grouping | |
| Included Contact Type: | |
| Round pin single mating end single contact grouping | |
| Precious Material And Location: | |
| Contact surfaces gold and contact surfaces silver | |
| Precious Material And Weight: | |
| 0.065 gold grains, troy and 0.065 silver grains, troy | |
| Precious Material: | |
| Gold and silver | |
| Thread Series Designator: | |
| Unef | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |