Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-045-9614

# Thread Class:

2a and 2b

# **Thread Direction:**

Right-hand and right-hand

# Body Style:

Hood, side opening w/clamp

### **Overall Length:**

2.062 inches

#### **Overall Height:**

2.467 inches

#### **Overall Width:**

1.130 inches

#### **Environmental Protection:**

Moisture resistant and vibration resistant

### Cable Entrance Diameter:

0.340 inches

## Threaded Device Type:

Coupling facility

## Mating End Quantity:

1

### **Contact Position Arrangement Style:**

34 single mating end

# **Contact Removability:**

Removable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

### **Polarization Method:**

Jackscrew

### Shell Type:

Hood, side opening

### **Connector Locking Method:**

Jackscrew-socket

### Connector Cable Strain Relief Method:

Cable clamp

### Thread Length:

0.320 inches

# Thread Size:

0.138 inches and 0.138 inches

### **Terminal Location:**

Back single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

NSN 5935-01-045-9614

Electrical Plug Connector - Page 2 of 2



**Terminal Type:** 

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

### **Included Contact Quantity:**

34 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.034 gold grains, troy

**Precious Material:** 

Gold

#### **Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:** 

Unc and unc

**Specification Data:** 

81349-mil-c-28748/4 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0