## NSN 5935-01-046-0101

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-046-0101 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.172 inches and 1.222 inches **Overall Height:** Between 1.117 inches and 1.133 inches **Overall Width:** Between 1.117 inches and 1.133 inches **Environmental Protection:** Moisture resistant and pressure proof and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.126 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.901 inches and 0.911 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.901 inches and 0.911 inches **Distance From Mounting Shoulder To Front Face:** Between 0.765 inches and 0.775 inches **Threaded Device Type:** Back shell **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 14-19 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 102.0 and 132.0 and 248.0 and 320.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi):

28

**Thread Size:** 

0.875 inches

## NSN 5935-01-046-0101

Electrical Receptacle Connector - Page 2 of 2

Qq-a-367, comp t6 federal specification single material response

**Included Contact Quantity:** 

**Precious Material And Location:** 

**Precious Material And Weight:** 

**Included Contact Type:** 

Contact surface gold

0.019 gold grains, troy **Precious Material:** 

**Test Data Document:** 

**Thread Series Designator:** 

81349-mil-c-81511/51 government specification

**Specification Data:** 

**Unit Of Measure:** 

Demilitarization:

Mil-g-45204 spec.

Mil-std (military Standard):

Shelf Life:

Gold

Un

N/a

No Fiig: A039b0

19 single mating end single contact grouping

Round pin single mating end single contact grouping



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Chromium
Shell Material Specification:

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).