single mating end



View Online at https://aerobasegroup.com/nsn/5935-01-046-0665

Body Style:	
Straight type	
Overall Length:	
4.350 inches	
Overall Height:	
0.565 inches	
Overall Width:	
0.250 inches	
Unthreaded Mounting Hole Diameter:	
0.120 inches	
Distance Between Mounting Facility Centers:	
4.100 inches	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
2 rows of contacts non-inserted board single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
5.0 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
1000.0 single mating end single contact grouping	
Polarization Method:	
Guide pin/socket	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping	
Insert Material:	
Plastic diallyl phthalate single mating end	
Contact Surface Treatment Specification:	
Mil-g-45204 military specification single treatment response single mating end single contact grouping	
Terminal Type:	
Solder well single mating end single contact grouping	
Contact Material Specification:	
Qq-c-530 federal specification single material response single mating end single contact grouping	
Guide Design And Location:	
D shape socket left-hand at 3 oclock and d shape pin right-hand at 3 oclock	
Insert Material Specification:	
Mil-p-19833 military specification single material response single mating end or mil-m-14f military specification single material response	Э



Included Contact Quantity:

50 single mating end single contact grouping

### Included Contact Type:

Round socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.050 gold grains, troy

## **Precious Material:**

Gold

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.