Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-046-2616

2b Thread Direction: Right-hand Body Style: Straight shape
Right-hand Body Style:
Body Style:
Straight shape
Overall Length:
4.650 inches
Overall Height:
0.849 inches
Overall Width:
Between 0.542 inches and 0.552 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.112 inches
Distance Between Mounting Facility Centers:
4.288 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1300.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
nternally threaded shell
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
nsert Material:
Glass single mating end

## NSN 5935-01-046-2616 Electrical Receptacle Connector - Page 2 of 2



**Terminal Type:** Crimp single mating end single contact grouping Included Contact Quantity: 76 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Special Features:** Polarized at position b2 **Precious Material And Location:** Contact surface gold and contact surface silver **Precious Material And Weight:** 0.076 gold grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0