## NSN 5935-01-046-2618

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-046-2618

**Thread Class:** 

2a

**Body Style:** 

Round flange mount, external coupling

**Overall Length:** 

0.863 inches

**Distance From Mounting Shoulder To Rear Face:** 

0.100 inches

**Threaded Device Type:** 

Coupling facility

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Wk-q1 single mating end

**Contact Maximum Current Rating In Amps:** 

10.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

15000.0 single mating end single contact grouping

**Connector Locking Method:** 

Externally threaded shell

Thread Size:

0.312 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-626, comp 360 federal specification single material response single mating end single contact grouping

**Shell Material:** 

Plastic diallyl phthalate

**Shell Material Specification:** 

Mil-m-14 military specification single material response

**Included Contact Quantity:** 

1 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-01-046-2618

Electrical Receptacle Connector - Page 2 of 2



Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.