## NSN 5935-01-046-2622

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-046-2622

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

5.305 inches

**Overall Height:** 

0.817 inches

**Overall Width:** 

0.330 inches

**Unthreaded Mounting Hole Diameter:** 

0.125 inches

**Distance Between Mounting Facility Centers:** 

5.045 inches

**Board Accommodated Length:** 

4.625 inches single board

**Board Accommodated Width:** 

0.062 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

800.0 single mating end single contact grouping

**Polarization Method:** 

Contact to contact polarizing keys

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Pin single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14 military specification single material response single mating end

**Included Contact Quantity:** 

72 single mating end single contact grouping

## NSN 5935-01-046-2622

Electrical Receptacle Connector - Page 2 of 2



included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.

Demilitarization: