Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-046-5426

| Thread Class   |
|--|
| Thread Class:  |
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Body Style:  |
| Straight shape, external coupling                              |
| Overall Length:  |
| 1.125 inches   |
| Overall Diameter:  |
| 0.812 inches   |
| Distance From Mounting Shoulder To Front Face:                 |
| 0.821 inches   |
| Mounting Facility Thickness:                                   |
| 0.250 inches   |
| Threaded Device Type:  |
| Mounting bushing   |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:                            |
| Uhf single mating end  |
| Contact Removability:  |
| Removable single mating end single contact grouping            |
| Contact Maximum Ac Voltage Rating In Volts:                    |
| 500.0 single mating end single contact grouping                |
| Contact Maximum Frequency Rating:                              |
| 11000.0 megahertz single mating end single contact grouping    |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 50.0 single mating end single contact grouping                 |
| Thread Size:   |
| 0.500 inches   |
| Terminal Location:   |
| Back single mating end single contact grouping                 |
| Terminal Type:   |
| Crimp single mating end single contact grouping                |
| Included Contact Quantity:                                     |
| 1 single mating end single contact grouping                    |
| Bushing Accommodation Hole Shape:                              |
| Round w/flat   |
| Thread Series Designator:                                      |
| Unef   |
| Shelf Life:  |
| N/a  |
|  |

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0