Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-046-6927

## Thread Class:

2b

**Thread Direction:** 

Right-hand

## Body Style:

Straight type

### **Overall Length:**

1.210 inches

#### **Overall Height:**

0.540 inches

## **Overall Width:**

0.531 inches

## **Distance Between Mounting Facility Centers:**

0.875 inches

#### **Threaded Device Type:**

# Mounting hole

Mating End Quantity:

1

## **Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

## Contact Removability:

Removable single mating end single contact grouping

# **Polarization Method:**

Contact

## **Connector Locking Method:**

Screw

#### **Thread Size:**

0.138 inches

## **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## Contact Surface Treatment Specification:

Mil-g-14548, type 2, class 1 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Tab, solder lug single mating end single contact grouping

# Included Contact Quantity:

4 single mating end single contact grouping

# Included Contact Type:

Leaf spring single mating end single contact grouping



**Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-14548 spec.