NSN 5935-01-047-1617



| Elect | trical Plug Connector - Page 1 of 2 | Group |
|--------|--|-------|
| View C | Online at https://aerobasegroup.com/nsn/5935-01-047-1617 | |
| Body | Style: | |
| Angle, | , shape, internal coupling | |
| Overa | all Length: | |
| 1.188 | inches | |
| Overa | all Height: | |
| 0.750 | inches | |
| Overa | all Diameter: | |
| 0.406 | inches | |
| Enviro | onmental Protection: | |
| Moistu | ure resistant | |
| Mating | g End Quantity: | |
| 1 | | |
| Conta | act Position Arrangement Style: | |
| Nonst | d single mating end | |
| Conta | act Removability: | |
| Remov | vable single mating end single contact grouping | |
| Conta | act Maximum Ac Voltage Rating In Volts: | |
| 750.0 | single mating end single contact grouping | |
| Polari | ization Method: | |
| Keywa | ay or multiple keyway | |
| Insert | t Position In Deg: | |
| 120.0 | | |
| Shell | Туре: | |
| Solid | | |
| Conne | ector Locking Method: | |
| Bayon | net latch | |
| Conne | ector Cable Strain Relief Method: | |
| Compi | pression nut | |
| Termi | inal Location: | |
| Back s | single mating end single contact grouping | |
| Termi | inal Type: | |
| Crimp | single mating end single contact grouping | |
| Shell | Material: | |
| Conne | er allov | |

Copper alloy

Shell Surface Treatment:

Gold and silver

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Shell surface gold and shell surface silver

NSN 5935-01-047-1617

Electrical Plug Connector - Page 2 of 2



| Precious Material And Weig | ght: |
|----------------------------|------|
|----------------------------|------|

0.100 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0