Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-047-1702

Thread Class: 2b Thread Direction: Right-hand Overall Height: 1.320 inches Overall Width: 1.320 inches Cable Opening Diameter: Between 0.406 inches and 0.750 inches Cable Opening Quantity: 1 Stace Designation: 1 1 Stace Designation: 1 1 Mouning Facility Type And Quantity: 1 threaded Coupling Thread Size: 1.125 inches State Treatment: Nickel Style Designator: Straight type wicable clamp Surface Treatment: Nickel Thread Streise Designator: Un Statight type wicable clamp Surface Treatment: Nickel Style Designator: Un Straight type wicable clamp Surface Treatment: Nickel Style Designator: Un Straight type wicable clamp Surface Treatment: Nickel Style Designator: Un Straight type wicable clamp Surface Treatment: Nickel Style Designator: Un Straight type wicable clamp Surface Treatment: Nickel Strai	Thread Classe	
Thread Direction: Right-hand Overall Height: 1.320 inches Overall Width: 1.325 inches Cable Opening Diameter: 1.325 inches Cable Opening Quantity: 1 Size Designation: 1 1 Size Designation: 18 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Material: Auterial: Auterial: Auterial: Stradget Type wickable clamp Size Treatment: Nickel Stradget Type wickable clamp Stradget		
Right-hand Overall Height: 1.320 inches Overall Width: 1.355 inches Cable Opening Diameter: Between 0.406 inches and 0.750 inches Cable Opening Quantity: 1 Size Designation: 1 Size Designation: 18 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.125 inches Adurinum alloy Surface Treatment: Nickel Strig type wickele clamp Surface Treatment: Nickel Thread Size: Surface Treatment: Nickel Strig type wickele clamp Butter Treatment: Nickel Thread Size: Interd Size: Nickel Thread Size: Nickel Thread Size: Surface Treatment: Nickel Thread Size: Surface Treatment: Nickel Thread Size: Surface Treatmen		
Nevrall Height:1.320 inchesOverall Width:1.255 inchesCable Opening Diameter:Between 0.406 inches and 0.750 inchesCable Opening Quantity:1Size Designation:18Mouning Facility Type And Quantity:1 threaded couplingThready Qly Per Inch (tpi):28Carlea Opening Classics1.125 inchesMouning Facility Type And Quantity:1.25 inchesMarcia:1.125 inchesMurnium alloySurface Treatment:NickelStright type wicable clampStright type wicable clampNickelChread Stries:NickelInde Stries:NickelChread Stries:NickelStright type wicable clampChread Stries:NickelChread Stries:NickelStright type wicable clampStright type wicable type wicable clampStright type wicable type wicable type wicable type wicable type wicable type wicable typ		
1.320 inclusi Overall Width: 1.255 inclusi Cable Opening Diameter: Between 0.406 incluss and 0.750 inclusis Cable Opening Quantiy: Cable Opening Quantiy: 1 Size Designation: 18 Mounting Facility Type And Quantiy: 1 threaded coupling Thready Qy Per Inch (tpi): 28 Threaded scupling Threaded Size: 1.125 inclusi Material: Aluminum alloy Surface Treatment: Nickel Sturface Treatment: Nickel Surface Treatment: Nickel Thread Series Designator: Intertion: Nickel Surface Treatment: Nickel Surface Treatment: <tr< th=""><th></th><th></th></tr<>		
Nevrail Width: 1.255 inches 2 Able Opening Diameter: Between 0.406 inches and 0.750 inches Cable Opening Quantity: 1 Size Designation: 18 Mounting Facility Type And Quantity: 1 threaded coupling Thready Oty Per Inch (tpi): 28 Threaded Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Nickel Straight type wicable clamp Surface Treatment: Nickel Straight type wicable clamp Buff Life: Nickel Thread Series Designator: In Mickel Thread Series Designator: Nickel Surface Treatment: Nickel Thread Series Designator: Nickel Surface Treatment: Nickel Thread Series Designator: Nickel Surface Treatment: Nickel Surface Treatment: Nickel </th <th></th> <th></th>		
1.255 incles Cable Opening Diameter: Between 0.406 inches and 0.750 inches Cable Opening Quantity: 1 Stozeosignation: 18 Mounting Facility Type And Quantity: 1 threaded coupling Thready Cuyper Inch (tpi): 28 Thread Size: 1.125 inches Material: Auminum alloy Surface Treatment: Nickel Style Designator: Stratight type w/cable clamp Surface Treatment: Nickel Thread Series Designator: Nickel Stript The Series Designator: Nickel Stript The Series Designator: </th <th></th> <th></th>		
Cable Opening Diameter: Between 0.406 inches and 0.750 inches Cable Opening Quantity: Cable Opening Quantity: 1 Size Designation: 18 Mounting Facility Type And Quantity: 1 threaded coupling Threaded coupling Threaded coupling Threaded scoupling Threaded scoupling Autoriation 1.125 inches Material: Autoriation Autoriation Surface Treatment: Nickel Straight type w/cable clamp Surface Treatment: Nickel Straight type w/cable sclamp Surface Treatment: Nickel Thread Series Designator: In Straight type w/cable sclamp In Company Materiation: Nickel Thread Series Designator: In Straight type w/cable sclamp Int of Measure: Na Dit Of Measure: In Straight in the sclamp		
Between 0.406 inches and 0.750 inches Cable Opening Quantity: 1 Size Designation: 18 Mounting Facility Type And Quantity: 1 threaded coupling Threaded coupling Thready Oty Per Inch (tpi): 28 Thread Size: 1.125 inches Material: Atuminum alloy Surface Treatment: Nickel Straight type w/cable clamp Straight type w/cable clamp Infread Streis: Nickel Thread Streis: Natting: Straight type: Nickel Thread Streis: Nickel		
Cable Opening Quantity: 1 Size Designation: 18 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qay Per Inch (tpi): 28 Thread Size: 1.125 inches Material: Aturnium alloy Surface Treatment: Nickel Straight type w/cable clamp Surface Treatment: Nickel Straight type w/cable clamp Markial: Nickel Straight type w/cable clamp Markial: Nickel Thread Series Designator: Nickel Thread Series Designator: Nickel Surface Treatment: Nickel Thread Series Designator: Nickel Guitt of Measure: - - Pomiliarization: No Fig:		
1 Size Designation: 18 Mounting Facility Type And Quantity: 1 threaded coupling Thready Oty Per Inch (tpi): 28 Thread Size: 1.125 inches Material: Aturnium alloy Surface Treatment: Nickel Straight type w/cable clamp Surface Treatment: Nickel Straight type w/cable clamp Surface Treatment: Nickel Straight type w/cable clamp Chread Series Designator: Un Thread Series Designator: Via Duping Diping Nickel Straight type w/cable clamp Straight type w/cable clamp Chread Series Designator: Inter Company Diping Nickel Straight type w/cable clamp Straight type w/cable clamp Inter Company Inter Company Diping Nickel Straight type w/cable clamp Inter Company </th <th></th> <th></th>		
Size Designation: 18 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Nickel Straight type w/cable clamp Surface Treatment: Nickel Strafes Designator: Outring Series Designator: Nickel Thread Series Designator: Nickel Thread Series Designator: Un Suffice Treatment: Nickel Thread Series Designator: Un Suffice Treatment: Nickel Thread Series Designator: Un Suffice: Nickel Suffice: Nickel Suffice: Nickel Suffice: Nickel Suffice: Suffice: Suffice: Nickel Suffice:		
18 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Nickel Style Designator: Straface Treatment: Nickel Straface Treatment: Nickel Straface Treatment: Nickel Straface Treatment: Nickel Designator: Uin Straface Treatment: Nickel Thread Series Designator: Uin Shelf Life: Na Thet Of Measure: Image: No Fig:		
Nouting Facility Type And Quantity:1 threade couplingThready Qty Per Inch (tpi):28Thread Size:1.125 inchesMaterial:Aluminum alloySurface Treatment:NickelStright type w/cable clampStright type w/cable clampNickelThread Steise Designator:NickelDire Manuel DirectionOutDirectionNickelThread Steise Designator:OutDirectionNickelSteif Life:NickelDirectionDirectionNickelSteif Life:NickelDirectionNickelDirectionNickelDirectionNickelDirectionNickelSteif Life:NickelSteif Life:NickelSteif Life:NickelSteif Life:NickelSteif Life:NickelSteif Life:NickelSteif Life:Steif	-	
1 threaded coupling Thready Cty Per Inch (tpi): 28 7 thread Size: 1.125 inches Material: Aluminum alloy Surface Treatment: Nickel Stright type w/cable clamp Stright type w/cable clamp Nickel Thread Series Designator: Nickel Dit Of Measure: - Pemilitarization: No Fig:		
Thready Qty Per Inch (tpi):28Thread Size:1.125 inchesMaterial:Aluminum alloySurface Treatment:NickelStraight type w/cable clampSurface Treatment:NickelDiread Series Designator:UnShelf Life:N/aDiref Measure:TrePine:NaDiref Measure:ToFemilitarization:NoFig:		
28 Thread Size: 1.125 inches Material: Material: Aluminum alloy Surface Treatment: Nickel Straight type wicable clamp Surface Treatment: Nickel Thread Series Designator: Un Shelf Life: N/a Enlide Measure: Toread Series Designator: Mai Dir of Measure: Totage Thread Series Designator: Mai Dir of Measure: Toread Series Designator: Toread Series Designator: Mai Dir of Measure: Toread Series Designator: Toread Series Designator: Mai Mai Dir of Measure: Toread Series Designator: Toread Series Designator: Toread Series Designator: Mai Mai Mai Mai Mai Mai Mai Mai Mai <t< th=""><th></th><th></th></t<>		
Hread Size:1.125 inchesMaterial:Aluminum alloySurface Treatment:NickelStyle Designator:Straight type w/cable clampSurface Treatment:NickelThread Series Designator:UnShelf Life:N/aDint of Measure:Inter Surface Treatment:N/aDint of Measure:Inter Surface Treatment:Surface Treatment:N/aDint of Measure:Imater Surface		
1.125 inches Material: Material: Aluminum alloy Surface Treatment: Nickel Surface Treatment: Nickel Thread Series Designator: Un Shelf Life: N/a Din Shelf Life: Shelf Din Shelf		
Material:Aluminum alloySurface Treatment:NickelStrig Designator:Straight type w/cable clampSurface Treatment:NickelThread Series Designator:UnShelf Life:N/aUni Of Measure:-Mitteriation:NoFig:		
Aluminum alloySurface Treatment:NickelStyle Designator:Straight type w/cable clampSurface Treatment:NickelThread Series Designator:UnShelf Life:N/aDint Of Measure:NoFing:Na		
Surface Treatment:NickelStyle Designator:Straight type w/cable clampSurface Treatment:NickelTread Series Designator:UnShelf Life:N/aDint Of Measure:NoFine:NoFine:NoFine:Surface:S		
Nickel Style Designator: Straight type w/cable clamp Surface Treatment: Nickel Nickel Thread Series Designator: Un Shelf Life: N/a Via Dint Of Measure: Fig:		
Style Designator:Straight type w/cable clampSurface Treatment:NickelThread Series Designator:UnShelf Life:N/aUni Of Measure:Demilitarization:NoFig:		
Straight type w/cable clamp Surface Treatment: Nickel Thread Series Designator: Un Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
Surface Treatment:NickelThread Series Designator:UnShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:		
Nickel Thread Series Designator: Un Un Shelf Life: N/a Unit Of Measure: Demiltarization: No		
Thread Series Designator: Un Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
Un Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:		
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-	
N/a Unit Of Measure: Demilitarization: No Fiig:		
Unit Of Measure: Demilitarization: No Fiig:		
 Demilitarization: No Fiig:		
Demilitarization: No Fiig:		
No Fiig:		
Fiig:		
A10100		
	A10100	