

View Online at <https://aerobasegroup.com/nsn/5935-01-047-4698>

Body Style:

Straight shape, external coupling

Overall Length:

1.750 inches

Overall Diameter:

1.125 inches

Environmental Protection:

Moisture resistant and vibration resistant and salt water resistant

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

10.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

45.0

Shell Type:

Potting w/grounding lug

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Potting type

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Chromium

Included Contact Quantity:

19 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end 2nd contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.020 gold grains, troy and 0.020 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0