# NSN 5935-01-047-6997

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-047-6997

Body Style:
Straight shape
Overall Length:
1.511 inches
Overall Height:
3.111 inches
Overall Width:
2.001 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.112 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.783 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.437 inches
Distance From Mounting Shoulder To Front Face:
0.766 inches
Mating End Quantity:
2
Contact Position Arrangement Style:
40 all mating ends
Contact Removability:
Removable all mating ends single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 all mating ends single contact grouping
Polarization Method:
3 polarization posts
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -54.2 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back all mating ends single contact grouping
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Gold all mating ends single contact grouping
Insert Material:

Plastic all mating ends

# NSN 5935-01-047-6997

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, grade c, class 1 military specification single treatment response all mating ends single contact grouping

### **Terminal Type:**

Crimp all mating ends single contact grouping

## **Guide Design And Location:**

Hexagon shape male post left-hand at 6 oclock and hexagon shape male post center at 6 oclock and hexagon shape male post right-hand at 6 oclock

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium and chromate

**Shell Surface Treatment Specification:** 

Qq-p-416, type ii, class 3 federal specification all treatment responses

**Included Contact Quantity:** 

40 all mating ends single contact grouping

**Included Contact Type:** 

Round pin all mating ends single contact grouping

**Special Features:** 

Float mount

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.080 gold grains, troy

Precious Material:

. roorous materi

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No Fiig:

A039b0

AUSSDU

Mil-std (military Standard):

Mil-g-45204 spec.