## NSN 5935-01-048-0090

0.026 gold grains, troy

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-048-0090

Body Style:
Straight type
Overall Length:
2.150 inches
Overall Height:
0.550 inches
Overall Width:
0.250 inches
Environmental Protection:
Humidity resistant and shock proof and thermal shock resistant and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
1.900 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Glass single mating end and plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-14 sdg-f or mil-p-19833 gdi-30f military specification single material response single mating end
Included Contact Quantity:
26 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:

## NSN 5935-01-048-0090

**Precious Material:** 

Mil-std (military Standard):

Mil-m-14 spec.

Electrical Receptacle Connector - Page 2 of 2



Gold
Test Data Document:
81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-55302/57 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0