

View Online at <https://aerobasegroup.com/nsn/5935-01-048-7510>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

Between 0.980 inches and 1.020 inches

**Overall Height:**

Between 0.927 inches and 0.947 inches

**Overall Width:**

Between 0.927 inches and 0.947 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.135 inches and 0.145 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.705 inches and 0.715 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.705 inches and 0.715 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.640 inches and 0.680 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20-66 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Insert Position In Deg:**

15.0

**Contact Material:**

Nickel alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Contact Material Specification:**

Qq-w-390 federal specification single material response single mating end single contact grouping

**Included Contact Quantity:**

6 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

98230-0n190305-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.