Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-048-9258

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 1.406 inches and 1.471 inches
Overall Height:
Between 0.804 inches and 0.820 inches
Overall Width:
Between 0.804 inches and 0.820 inches
Environmental Protection:
Moisture resistant and pressure proof and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.126 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.589 inches and 0.599 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.589 inches and 0.599 inches
Distance From Mounting Shoulder To Front Face:
Between 0.894 inches and 0.906 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
40394 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
28
Thread Size:
0.500 inches

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:	
Back single mating end	I single contact grouping
Contact Material:	
Copper alloy single ma	ting end single contact grouping
Contact Surface Trea	tment:
Gold single mating end	single contact grouping
Contact Surface Trea	tment Specification:
Mil-g-45204 military sp	ecification single treatment response single mating end single contact grouping
Terminal Type:	
Crimp single mating er	d single contact grouping
Shell Material:	
Aluminum alloy 6061	
Shell Surface Treatme	ent:
Cadmium	
Shell Surface Treatme	ent Specification:
Qq-p-416, type 2, cl 3	federal specification single treatment response
Shell Material Specifi	cation:
Qq-a-367, comp 6061,	t6 federal specification single material response
Included Contact Qua	intity:
4 single mating end sir	gle contact grouping
Included Contact Typ	e:
Round pin single matin	g end single contact grouping
Precious Material And	d Location:
Contact surfaces gold	
Precious Material And	d Weight:
0.004 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-c-81511 spe	cification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes comr	nercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and per	ormance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Design	ator:
Unef	
Specification Data:	
81349-mil-c-81511/21	government specification
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Stand	lard):