NSN 5935-01-049-2247

Aluminum alloy

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-049-2247 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.234 inches **Overall Diameter:** 1.406 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 17-99 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch Thread Length: 0.219 inches **Thread Size:** 0.938 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:**

NSN 5935-01-049-2247

A039b0

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
21 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.023 gold grains, troy and 0.023 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: