## NSN 5935-01-049-7413

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-049-7413 **Body Style:** Straight shape, flush mount **Overall Length:** 1.157 inches **Overall Height:** 1.125 inches **Overall Width:** 2.312 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.062 inches **Mating End Quantity: Contact Position Arrangement Style:** 26 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** 

**Shell Surface Treatment:** Cadmium and chromate

Aluminum alloy

# NSN 5935-01-049-7413

Electrical Receptacle Connector - Page 2 of 2



### **Included Contact Quantity:**

26 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.026 gold grains, troy and 0.026 silver grains, troy

#### **Precious Material:**

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0