Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-049-7417

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.222 inches

Overall Height:

1.109 inches

Overall Width:

1.109 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.812 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.812 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

12 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Spring friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy



Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.012 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Demilitarization: No
Νο
No Fiig:
No Fiig: A039b0
No Fiig: A039b0 Mil-std (military Standard):
No Fiig: A039b0 Mil-std (military Standard):