

View Online at <https://aerobasegroup.com/nsn/5935-01-049-7910>

Body Style:

Hood, top opening w/clamp

Overall Length:

2.880 inches

Overall Height:

2.608 inches

Overall Width:

1.190 inches

Environmental Protection:

Humidity resistant and thermal shock resistant and vibration resistant

Cable Entrance Diameter:

Between 0.500 inches and 1.000 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

25-104 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Jackscrew

Shell Type:

Hood, top opening

Connector Locking Method:

Jackscrew-socket

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Metal single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy or stainless steel

Shell Material Specification:

Qq-a-250/8, alloy 5052, h32 federal specification single material response or qq-s-766, series 300 federal specification single material response

Insert Material Specification:

Mil-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

104 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.