## NSN 5935-01-050-1316

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-050-1316 **Thread Class:** 2b **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Gray **Body Style:** Threaded bushing mounted **Overall Length:** 0.880 inches **Body Length:** 0.750 inches **Overall Diameter:** 0.312 inches **Bushing Accommodation Hole Shape:** Round w/flat **Maximum Voltage Rating In Volts:** 1500.0 dc **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Bushing Thru-hole Accommodation Length:** 0.234 inches **Bushing Thru-hole Accommodation Width:** 0.250 inches **Current Rating In Amps: Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Terminal Type:** Turret

Material:

Steatite insulator

## NSN 5935-01-050-1316

Tip Jack - Page 2 of 2



Material:
Steatite insulator
Precious Material And Location:
Body and contact spring surfaces gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Surface Treatment:
Gold and nickel body
Surface Treatment:
Gold spring and nickel spring
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ03400