

View Online at <https://aerobasegroup.com/nsn/5935-01-050-3914>

**Thread Direction:**

Right-hand

**Body Style:**

Angle, shape, internal coupling

**Overall Length:**

0.609 inches

**Overall Height:**

0.750 inches

**Overall Diameter:**

0.250 inches

**Environmental Protection:**

Humidity resistant and shock proof and vibration resistant

**Cable Entrance Diameter:**

0.086 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.5 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Spring friction

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, class @2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy 360

**Shell Surface Treatment:**

Gold

**Shell Material Specification:**

Qq-b-626, 1/2 h federal specification single material response

**Insert Material Specification:**

L-p-403, type 1 assn standard single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact and body surfaces gold

**Precious Material And Weight:**

0.001 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.