Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-050-3923

Thread Class
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 0.860 inches and 0.890 inches
Overall Diameter:
Between 0.360 inches and 0.390 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Cable Entrance Diameter:
0.086 inches
Distance From Mounting Shoulder To Front Face:
Between 0.531 inches and 0.561 inches
Mounting Facility Thickness:
0.093 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.5 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Spring friction
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
40
Thread Size:
0.281 inches
Terminal Location:
Back single mating end single contact grouping



## **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Shell Material:** Copper alloy 360 **Shell Surface Treatment:** Gold **Shell Material Specification:** Qq-b-626, comp 360, 1/2 h federal specification single material response **Insert Material Specification:** L-p-403 federal specification single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact and body surface gold **Precious Material And Weight:** 0.101 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0