

View Online at <https://aerobasegroup.com/nsn/5935-01-050-4297>

Body Style:

Straight shape

Overall Length:

Between 1.526 inches and 1.556 inches

Overall Height:

0.663 inches

Overall Width:

Between 0.479 inches and 0.509 inches

Environmental Protection:

Corrosion resistant and moisture proof and shock resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Distance Between Mounting Facility Centers:

Between 1.307 inches and 1.317 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

15 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Included Contact Quantity:

15 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.015 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-24308/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.