NSN 5935-01-050-9056

Plastic diallyl phthalate single mating end

Thread Class:

2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-050-9056

Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.000 inches
Overall Diameter:
0.448 inches
Environmental Protection:
Moisture resistant and shock proof and vibration resistant
Cable Entrance Diameter:
Between 0.180 inches and 0.185 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Twin-x single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
78.0 single mating end single contact grouping
Thread Size:
0.375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:

NSN 5935-01-050-9056

Mil-std (military Standard):

Mil-m-14 spec.

Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Gold and copper
Shell Material Specification:
Qq-b-626 federal specification single material response
Insert Material Specification:
Mil-m-14 military specification single material response single mating end
Included Contact Quantity:
2 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact, terminal and shell surfaces gold
Precious Material And Weight:
0.110 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0