NSN 5935-01-051-3273

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-051-3273

Body Style:

Right angle type

Overall Length:

Between 4.080 inches and 4.100 inches

Overall Height:

Between 0.551 inches and 0.566 inches

Overall Width:

0.270 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant

Unthreaded Mounting Hole Diameter:

0.067 inches

Distance Between Mounting Facility Centers:

Between 3.765 inches and 3.775 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping and qq-b-613, comp 2 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape pin right-hand at 12 oclock

Insert Material Specification:

Mil-m-14, sdg-f military specification single material response single mating end

NSN 5935-01-051-3273

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 70 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.070 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.